## **DENTAL EXPRESS** ZINC OXIDE IMPRESSION PASTE

Made in England

Code 8028

**DENTAL EXPRESS** 

A high definition material based on Eugenol (catalyst paste) and Zinc Oxide (base paste).

INDICATIONS:

- The taking of impressions for the manufacture of dentures, particularly for 1. edentulous patients
- The taking of impressions to enable mal-fitting dentures to be relined.

MIXING:

Squeeze equal lengths of material with the aid of a key from catalyst, and base paste tubes (approximately 3 inches each for a lower and 4 inches for an upper impression). Use a broad stiff spatula and mix thoroughly with sweeping strokes until a uniform colour indicates a completely homogeneous material (mixing time 30 seconds). Mix ratio: 2.75:1 by weight (base: catalyst). NB: Replace caps after extruding paste. Working time: 2 minutes at 23°C from end of mix

IMPRESSION TAKING:

Apply mixed material to entire surface of a special tray (for denture manufacture) or to the thoroughly cleaned surface of existing denture (for refining). Setting time: 2 to 2 1/2 minutes at 37°C

CLEANING:

Clean and disinfect the impression using Perform – ID (Schülke & Mayr) following the instructions on the packet. The material can be removed from spatulas using alcohol. (Caution: HIGHLY FLAMMABLE).

CAUTION:

This material contains Eugenol and like all such materials may occasionally cause the patient to experience short-lived mucosal irritation. Avoid contact with eyes - if this occurs, wash with copious quantities of water and seek medical attention.

STORAGE:

Store in a cool dry place 5-25°C. BATCH CODE:

The batch code gives the date of manufacture in month, year, and day format with a number suffix to uniquely identify the batch of material. The number must be quoted in all correspondence

SPECIALLY FORMULATED FOR USE IN DENTISTRY

PRESENTATION: 165g Base / 60g Catalyst 010166

Distributed by: Distribuido por: Distribue par: Vertrieb durch:

DE Healthcare Products., Gillingham ME8 0SB U.K.

Denver PA 17517 USA

ZINC OXIDE IMPRESSION PASTE A high definition material based on Eugenol (catalyst paste) and Zinc Oxide (base

paste). INDICATIONS:

- The taking of impressions for the manufacture of dentures, particularly for edentulous patients.
- The taking of impressions to enable mal-fitting dentures to be relined.

MIXING:

Squeeze equal lengths of material with the aid of a key from catalyst, and base paste tubes (approximately 3 inches each for a lower and 4 inches for an upper impression). Use a broad stiff spatula and mix thoroughly with sweeping strokes until a uniform colour indicates a completely homogeneous material (mixing time 30 seconds). Mix ratio: 2.75:1 by weight (base: catalyst). NB: Replace caps after extruding paste. Working time: 2 minutes at 23°C from end of mix

IMPRESSION TAKING:

Apply mixed material to entire surface of a special tray (for denture manufacture) or to the thoroughly cleaned surface of existing denture (for refining). Setting time: 2 to 2 1/2 minutes at 37°C

CLEANING:

Clean and disinfect the impression using Perform – ID (Schülke & Mayr) following the instructions on the packet. The material can be removed from spatulas using alcohol. (Caution: HIGHLY FLAMMABLE).

CAUTION:

This material contains Eugenol and like all such materials may occasionally cause the patient to experience short-lived mucosal irritation. Avoid contact with eyes - if this occurs, wash with copious quantities of water and seek medical attention.

STORAGE:

Store in a cool dry place 5-25°C. BATCH CODE:

The batch code gives the date of manufacture in month, year, and day format with a number suffix to uniquely identify the batch of material. The number must be quoted in all correspondence

SPECIALLY FORMULATED FOR USE IN DENTISTRY

PRESENTATION: 165g Base / 60g Catalyst 010166

Distributed by: Distribuido por: Distribue par: Vertrieb durch:

DE Healthcare Products., Gillingham ME8 0SB U.K. Denver PA 17517 USA

Made in England Code 8028

## **DENTAL EXPRESS**

ZINC OXIDE IMPRESSION PASTE A high definition material based on Eugenol (catalyst paste) and Zinc Oxide (base

paste). INDICATIONS:

- The taking of impressions for the manufacture of dentures, particularly for edentulous patients.
  The taking of impressions to enable mal-fitting dentures to be relined.

MIXING:

Squeeze equal lengths of material with the aid of a key from catalyst, and base paste tubes (approximately 3 inches each for a lower and 4 inches for an upper impression). Use a broad stiff spatula and mix thoroughly with sweeping strokes until a uniform colour indicates a completely homogeneous material (mixing time 30 seconds). Mix ratio: 2.75:1 by weight (base: catalyst). NB: Replace caps after extruding paste. Working time: 2 minutes at 23°C from end of mix

MMPRESSION TAKING:
Apply mixed material to entire surface of a special tray (for denture manufacture) or to the thoroughly cleaned surface of existing denture (for refining). Setting time: 2 to 2 1/2 minutes at 37°C

CLEANING:

Clean and disinfect the impression using Perform - ID (Schülke & Mayr) following the instructions on the packet. The material can be removed from spatulas using alcohol. (Caution: HIGHLY FLAMMABLE).

CAUTION:

This material contains Eugenol and like all such materials may occasionally cause the patient to experience short-lived mucosal irritation. Avoid contact with eyes - if this occurs, wash with copious quantities of water and seek medical attention. STORAGE:

Store in a cool dry place 5-25°C.

BATCH CODE:

The batch code gives the date of manufacture in month, year, and day format with a number suffix to uniquely identify the batch of material. The number must be quoted in

SPECIALLY FORMULATED FOR USE IN DENTISTRY

PRESENTATION: 165g Base / 60g Catalyst 010166

Distribuido por: Distributed by: Distribue par: Vertrieb durch:

DE Healthcare Products., Gillingham ME8 0SB U.K.

Denver PA 17517 USA

Made in England Code 8028

## **DENTAL EXPRESS** ZINC OXIDE IMPRESSION PASTE

A high definition material based on Eugenol (catalyst paste) and Zinc Oxide (base paste). INDICATIONS:

- The taking of impressions for the manufacture of dentures, particularly for edentulous patients.
  The taking of impressions to enable mal-fitting dentures to be relined.
- MIXING:

Squeeze equal lengths of material with the aid of a key from catalyst, and base paste tubes (approximately 3 inches each for a lower and 4 inches for an upper impression). Use a broad stiff spatula and mix thoroughly with sweeping strokes until a uniform colour indicates a completely homogeneous material (mixing time 30 seconds). Mix ratio: 2.75:1 by weight (base: catalyst). NB: Replace caps after extruding paste. Working time: 2 minutes at 23°C from end of mix

IMPRESSION TAKING:

Apply mixed material to entire surface of a special tray (for denture manufacture) or to the thoroughly cleaned surface of existing denture (for refining). Setting time: 2 to 2 1/2 minutes at 37°C

CLEANING:

Clean and disinfect the impression using Perform - ID (Schülke & Mayr) following the instructions on the packet. The material can be removed from spatulas using alcohol. (Caution: HIGHLY FLAMMABLE).

CAUTION:

This material contains Eugenol and like all such materials may occasionally cause the patient to experience short-lived mucosal irritation. Avoid contact with eyes - if this occurs, wash with copious quantities of water and seek medical attention. STORAGE:

Store in a cool dry place 5-25°C.

BATCH CODE:

The batch code gives the date of manufacture in month, year, and day format with a number suffix to uniquely identify the batch of material. The number must be quoted in all correspondence.
SPECIALLY FORMULATED FOR USE IN DENTISTRY

PRESENTATION: 165g Base / 60g Catalyst

Distributed by: Distribuido por:

Distribue par: Vertrieb durch:
DE Healthcare Products., Gillingham ME8 0SB U.K.

Denver PA 17517 USA

Made in England Code 8028